



Version number: 2

Replaces SDS: 2013-03-11

Issued: 2016-04-04

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name P45S

Article No. 7145-XXXX

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product type SMAW Un- and Low-alloyed electrodes

Use Arc welding

1.3 Details of the supplier of the safety data sheet

Supplier Elga AB

Street address Box 277

433 25 Partille

Sverige

Telephone 031 726 46 00

Fax 031 726 47 00

Email sds@elga.se

Web site www.elgawelding.com

Email sds@elga.se

1.4 Emergency telephone number

Available outside office hours Yes

Emergency phone number 911 / 112

Other

Web site: www.elgawelding.com

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Description The form of this product does not contribute to a hazard classification of the product.

2.2 Label elements



Version number: 2

Replaces SDS: 2013-03-11

Issued: 2016-04-04

The product do not require labeling

2.3 Other hazards

This product contains: Nickel as classified as sensitizing and Limited evidence of a carcinogenic effect. The form of this product does not contribute to a hazard classification of the product.

When the product is used in the welding process the most important hazards are:

Overexposure to fumes and gases from welding can be dangerous to health.

Watch out for splatter, hot metal and slag. It may cause skinburn and cause fire.

Arc rays can injure eyes and burn skin.

Electric shock: can kill. Avoid touching live electrical parts.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Chemical name	CAS No. EC No. REACH No.	Concentration	Classification	H-phrase
Kaolin	1332-58-7 - -	<20%	-	-
manganese	7439-96-5 231-105-1 01-2119449803-34-XXXX	<20%	-	-
Aluminium oxide	1344-28-1 215-691-6 01-2119529248-35-XXXX	<5%	-	H335

Substance additional information

For the full text of the H phrases mentioned in this Section, see Section 16.

SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms occur.



Version number: 2

Replaces SDS: 2013-03-11

Issued: 2016-04-04

Skin contact Burns should be treated by doctor.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. Burns from radiation, see doctor.

Ingestion Contact a doctor if more than an insignificant amount has been swallowed.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons.

4.3 Indication of any immediate medical attention and special treatment needed

Not applicable

SECTION 5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media carbon dioxide (CO2), powder or Diffuse jet of water. In case of major fire: Extinguish fire with

Diffuse jet of water or foam.

5.2 Special hazards arising from the substance or mixture

Not applicable

5.3 Advice for firefighters

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

General ventilation and local fume extraction must be adequate to keep fume concetrations within safe limits. . Use repiratory equipment when welding in a confined space. Wear protective clothing and eye protection appropriate to arc welding. . Skin contact should be avoided to prevent possible allergic reactions. .

6.2 Environmental precautions

Try to prevent the material from entering drains or water courses.

6.3 Methods and material for containment and cleaning up

Not applicable

6.4 Reference to other sections

Personal protection see section 8 and for disposal see section 13. Environmental precautions, Paragraph 12. Se also section 7



Version number: 2

Replaces SDS: 2013-03-11

Issued: 2016-04-04

Precautions for safe handling.

SECTION 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Preventive handling precautions	Ensure adequate ventilation for the welder and others. Use repiratory equipment when welding in a confined space. Wear protective clothing and eye protection appropriate to arc welding. Remove all flammable materials and liquids before welding.
General hygiene	Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Store welding consumables inside a room without humidity. Do not store welding consumables directly on the ground or beside walls. Store away from chemical substances like acids which could cause chemical reactions.

7.3 Specific end use(s)

welding process

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

National	occupa	tional
ex	kposure	limits

Ingredient	CAS no.	EC No.	Expos e limit mg/m: ppm		Short- expos mit mg/m	ure li	Remark	Source	Year
Aluminium ox ides	1344-2 8-1	215-6 91-6	10	1	1	1	inhalable d ust	EH40/2005 Wor kplace exposure limits	-
Aluminium ox ides	1344-2 8-1	215-6 91-6	4	1	1	-	respirable dust	EH40/2005 Wor kplace exposure limits	-
Kaolin	1332-5 8-7	-	2	-	-	-	respirable dust	EH40/2005 Wor kplace exposure limits	-



Version number: 2

Replaces SDS: 2013-03-11

Issued: 2016-04-04

Technical precaution measures	General ventilation and local fume extraction must be adequate to keep fume concetrations within safe limits
Eye / face protection	Wear eye protection appropriate for welding.
Safety gloves	Skin contact should be avoided to prevent possible allergic reactions
Other skin protection	Wear body protection which help to prevent injury from radiation, sparks and electric shock.
Respiratory protection	Use repiratory equipment when welding in a confined space. Wear protective clothing and eye protection appropriate to arc welding.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance, colour	grey
Appearance, physical state	Rod
Auto-ignition temperature	Not applicable
Autoinflammability	not auto-flammable
Decomposition temperature	Not applicable
Evaporation rate	Not applicable
Explosive properties	Not explosive
Flammability (solid, gas)	Not applicable
Flash point	Not applicable
Form	Fast
Initial boiling point and boiling range	Not applicable
Melting point / freezing point	Not applicable
Odour	odourless
Odour treshold	Not applicable
Oxidising properties	Not applicable
Partition coefficient: n-octanol / water	Not applicable
pH value	Not applicable
Relative density	Not applicable



Version number: 2

Replaces SDS: 2013-03-11

Issued: 2016-04-04

9.2 Other information

Not applicable

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity

Not applicable

10.2 Chemical stability

Stable at normal conditions

10.3 Possibility of hazardous reactions

Not applicable

10.4 Conditions to avoid

None under normal conditions.

10.5 Incompatible materials

Not applicable

10.6 Hazardous decomposition products

Welding fumes and gases. Additional fume may arise from coatings and contaminants on the base material.

Fume analysis: wt %

Fe 25-35

Mn <10

Ni <0,1

Cr <0,1

Cu <0,2

Pb <0,1

F-



Version number: 2

Replaces SDS: 2013-03-11

Issued: 2016-04-04

Refer to applicable national exposure limits for welding fume and its compounds.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Conditions to avoid: none in the form supplied.

When welding, fumes and gases generated can be dangerous to health.

Acute toxicity	Excessive exposures may affect human health, as follows: Aspiration may cause pulmonary oedema and pneumonitis. Short-term ovverexposure can cause dizziness, nausea and irritation of the nose, throat or eyes.
Irritation	Not applicable
Corrosive effects	Not applicable
Sensitisation	May cause sensitization by skin contact.
Mutagenicity	Not applicable
Carcinogenicity	Welding fumes are possibly carcinogenic to humans.
Repeated dose toxicity	Not applicable
Reproductive toxicity	Not applicable

SECTION 12. ECOLOGICAL INFORMATION

12.1 Toxicity

The welding process can effect the environment if fume is released directly into the atmosphere. Residues from welding consumables could degrade and accumulate into soils and ground water.

Acute fish toxicity	LC50 Fish 96h: Maganese: 2,91 mg/l Aluminiumoxide: >100 mg/l Salmo trutta
Acute algae toxicity	IC50 Algae 72h: Maganese: 0,55 mg/l Aluminiumoxide: >100 mg/l Selenastrum capricornutum (green algae)
Acute crustacean toxicity	EC50 Daphnia 48h: Maganese: 5,2 mg/l Aluminiumoxide: >100 mg/l Daphnia magna (Water flea)

12.2 Persistence and degradability

Not applicable

12.3 Bioaccumulative potential



Version number: 2

Replaces SDS: 2013-03-11

Issued: 2016-04-04

Bioconcentration factor (BCF):

iron: 140000 Maganese: 59052

12.4 Mobility in soil

Not applicable

12.5 Results of PBT and vPvB assessment

Not applicable

12.6 Other adverse effects

Not applicable

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal considerations Dispose of any product, residue or packing material according to national and local regulations.

Spent fume extraction filters shall be disposed of as dangerous waste.

Other

Waste code (EWC) 12 01 13 - welding waste

SECTION 14. TRANSPORT INFORMATION

14.1 UN number

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Not applicable

14.6 Special precautions for user



Version number: 2

Replaces SDS: 2013-03-11

Issued: 2016-04-04

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations	The product does not need to be labelled in accordance with EC directives or respective national laws.
National regulations	EH40/2005 Workplace exposure limits Waste Ordinance (2011:927)
	Local laws and regulations should be carefully observed.

15.2 Chemical safety assessment

Not applicable

SECTION 16. OTHER INFORMATION

Changes to previous revision	Changes are made in the following sections: 2, 3, 15 och 16.
References to key literature and data sources	Regulation (EC) No 1907/2006 of the European Parliament and of the Council, (REACH). Regulation (EC) No 1272/2008 of the European Parliament and of the Council. EH40/2005 Workplace exposure limits. Waste Ordinance (2011:927). www.prevent.se C&L Inventory database Annex VI CLP Regulation (EC) 1272/2008
Phrase meaning	H335 - May cause respiratory irritation.
Other	
Manufacturer's notes	Read this Safety Data Sheet carefully and become aware of hazards implied and the Safety information.