

MultiFLOW Air & Fluid Gun – Series 210

- **Unmatched blowing force**
- **Adjustable flow control**
- **Adjustable beam**

CEJN's MultiFLOW blowgun effectively cleans surfaces with air or water with unparalleled blowing force. Precise flow is achieved by adjustable flow settings. Nozzle adjusts from narrow jet to wide beam. The MultiFLOW meets and exceeds OSHA safety standards when dead-ended.








CEJN Safety

TECHNICAL DATA

Material blowgun	POM, TPE, Aluminum
Media	Air and non-explosive water based liquids
Material seal	NBR (Nitrile)
Max. working pressure	232 PSI (16 bar)
Min. burst pressure	64 bar (928 PSI)
Temperature range	140°F – +176°F (60°C – +80°C) 10 Working pressure
Temperature range	-4°F – +140°F (-20°C – +60°C) 16 Working pressure
Sound level	79 dB - 101 dB

Flow capacity is measured at 87 PSI (6 bar) inlet pressure.

	Part No.	Connection	Air flow min-max	Fluid flow min-max
ADJUSTABLE JET 	11 210 0400	320 nipple	200 - 1200 l/min (7.1 – 42.4 CFM)	5 - 25 l/min (1.3 – 6.6GPM)
	11 210 0430	Fluid nipple	200 - 1200 l/min (7.1 – 42.4 CFM)	5 - 25 l/min (1.3 – 6.6GPM)
	11 210 0450	1/4" female	200 - 1200 l/min (7.1 – 42.4 CFM)	5 - 25 l/min (1.3 – 6.6GPM)
	11 210 0455	1/2" fem fluid	200 - 1200 l/min (7.1 – 42.4 CFM)	5 - 25 l/min (1.3 – 6.6GPM)
STRAIGHT TUBE 90 MM 	11 210 0100		150 - 1100 l/min (5.3 – 38.8 CFM)	
	11 210 0150		150 - 1100 l/min (5.3 – 38.8 CFM)	
	11 210 0152		150 - 1100 l/min (5.3 – 38.8 CFM)	
STAR-TIPTUBE 90 MM 	11 210 3100		100 - 700 l/min (3.5 – 24.7 CFM)	
	11 210 3150		100 - 1100 l/min (3.5 – 38.8 CFM)	
	11 210 3152		100 - 1100 l/min (3.5 – 38.8 CFM)	
ADJUSTABLE FLUID 	11 210 0340			3.5 - 15 l/min (0.9 – 4.0GPM)
	11 210 0352			3.5 - 15 l/min (0.9 – 4.0GPM)
	11 210 0355			3.5 - 15 l/min (0.9 – 4.0GPM)
EIGHT-PACK DISPLAY 	11 210 9980	320 nipple	200 - 1200 l/min (7.1 – 42.4 CFM)	5 - 25 l/min (1.3 – 6.6GPM)
	11 210 9981	1/4" female	200 - 1200 l/min (7.1 – 42.4 CFM)	5 - 25 l/min (1.3 – 6.6GPM)

CEJN reserves the right to make changes without further notification. Thread connections are listed according to ISO Standards. Other connections and sealing material on request. Check with an authorized CEJN distributor for availability and prices. Some part numbers may be subject to minimum order quantities. Please visit our website, www.cejn.us, for general maintenance